

SHINKO

MOTORCYCLE TIRES

R012 Race Tyre

Tyre Pressure Table

	RIM RECOMMENDED (INCHES)	PRESSURE RANGE RECOMMENDED (COLD) BAR (PSI)	PRESSURE RANGE RACCOMENDED (HOT) BAR (PSI)	TYRE WARMERS USE °C (°F)
FRONT 110/70 ZR17	RIM RECOMMENDED (INCHES)3.00	PRESSURE RANGE RECOMMENDED (cold) bar (psi)2.0/2.2 (29/32)	PRESSURE RANGE RECCOMENDED (HOT) bar (psi)2.1/2.4 (30/35)	TYRE WARMERS USE °C (°F)50 MINS. @ 80 °C (176°F)
REAR 140/70 ZR17	RIM RECOMMENDED (INCHES)3.75/4.00	PRESSURE RANGE RECOMMENDED (cold) bar (psi)1.6/1.8 (23/26)	PRESSURE RANGE RECCOMENDED (HOT) bar (psi)1.7/1.9 (25/28)	TYRE WARMERS USE °C (°F)50 MINS. @ 80 °C (176°F)
REAR 150/60 ZR17	RIM RECOMMENDED (INCHES)4.00 - 4.25	PRESSURE RANGE RECOMMENDED (cold) bar (psi)1.6/1.8 (23/26)	PRESSURE RANGE RECCOMENDED (HOT) bar (psi)1.7/1.9 (25/28)	TYRE WARMERS USE °C (°F)50 MINS. @ 80 °C (176°F)

Tyre specs

Tyre Size	Overall Diameter	Width (inches)
110/70-17	23.07	4.33
140/70-17	24.72	5.47
150/60-17	24.09	5.94